

Install 2" Cap:

1/8" hex key to secures cap with 1/4" set screw

Socket/Lamp height adjustment:

- Loosen screw securing socket mounting strap
- Slide mounting strap to reposition led lamp
- Tighten screw against flange nut

LED bipin lamp - **12 volt standard**-

- Use single diode lamp for best shadow patterns

Corner tube routes lead wires to base where they exit fixture corner

Base Plate Assembly:

Threaded pipe nipple with lock ring and pipe cap secures 2x2 on top of stake

Attraction Lights 2x2 Series Install

To see this detail up close or print:
 AttractionLights.com - Resources menu -
 Installation Guides - 2x2 Series
 info@attractionlights.com
 970-316-0019 Lyle Braund

Lifetime Guarantee Void if soil and/or mulch covers fixture metal base - hide stake with mulch

Soil level at or below top of stake!



Sun Design



Socket Assembly Install

Step 1: Slide lead wires thru corner tube and out base of fixture

Step 2: Install bipin led lamp in socket

Step 3: Install screw (10x24x3/8" Philips) with flange nut (loose) thru fixture back plate

Step 4: Slide socket mounting strap tabs behind flange nut then tighten screw. Note: Tip mounting strap to help flange nut "grab."

- Position tip of led lamp just above above design space for maximum light spread + lamp shielding

Step 5: Leave a loop of wire lead in top for ease of future lamp change

Base Plate Assembly Install

- 2x2 shipped with base plate and threaded pipe for securing to stake installed

Step 2: Thread pipe exiting base of 2x2 into stake until stake pulls tight against 2x2 base.
- Do not over tighten as the metal thread can easily strip the plastic thread

NOTE: Hold wires out of the way while threading 2x2 onto stake
- Wires exit fixture corner and through stake slot

Step 1: Install stake; also see text on stake
- 13 inch "Hammer Stake" driven into soft soil with rubber mallet
- Take care that the stake top is level or the light fixture will not be plumb when installed

